



CUT AND PANEL REPLACEMENT DETERMINATION:

FULL CEMENT CONCRETE PANEL REPLACEMENT: FOR CEMENT CONCRETE SURFACE STREETS, THE MINIMUM RESTORATION SHALL BE FULL PANEL REPLACEMENT, IF ONE OR MORE OF THE FOLLOWING CONDITIONS EXIST:

	Less than ten (10) yrs old	Ten (10) yrs or older	Additional Requirements
Local Access without Bus Route	No	No	
Local Access with Bus Route	Yes	Yes	
Intersection (All Streets)	Yes	Yes	Plus one panel beyond the curb return
40% Removal	Yes	Yes	
Excellent Condition (based on visual and/or non-destructive testing)	Yes	Yes	
Principal, Minor, Collector Arterial and all streets in CBD and all bus route	Yes, If twenty-four (24) square feet or more of any panel needs to be patched	Yes, If twenty-four (24) square feet or more of any panel needs to be patched	

*CDF BACKFILL MAY BE USED IN LIEU OF RESTORING EXISTING RIGID BASE AT THE DISCRETION OF THE ENGINEER.

TYPICAL PATCH FOR RIGID PAVEMENT PAVEMENT PATCHING AND RESTORATION DETAIL



ADOPTED
CITY OF RENTON
STANDARD PLANS
LST DATE: 04/04

DATE	REVISION	BY	APPR'D

DWG. NAME: H033

SP PAGE: H033